


2025



PRODUCT CATALOG

WWW.CHAMPIONMETALSUPPLY.COM | ADDRESS : 2527 HWY 22, RIVERSIDE, IA. 52327 | PHONE 319-331-1618

TABLE OF CONTENTS




AG PANEL

PAGE 1

AG PANEL TRIMS

PAGE 2-4



PBR PANEL

PAGE 5

PBR PANEL TRIMS

PAGE 6-8



FF100 STANDING SEAM

PAGE 9

FF100 STANDING SEAM TRIM

PAGE 10-12




FF150 STANDING SEAM

PAGE 13

FF150 STANDING SEAM TRIM

PAGE 14-16



SS200 STANDING SEAM

PAGE 17

SS200 STANDING SEAM TRIM

PAGE 18-20



BOARD & BATTEN

PAGE 21

BOARD & BATTEN TRIMS

PAGE 22-23



ROOFING ACCESSORIES

PAGE 24-31


COLOR CHART

PAGE 32-35

ABOUT US

PAGE 36

TRIMS PLACEMENT




AG PANEL

CMS AG Panel

Exposed Fastener System

A durable, economical roofing solution for agriculture, commercial and residential projects. This type of panel is weather-resistant to increase the life of your roof. AG panels are attached with exposed fasteners used for roof and wall systems. Providing high weather-resistant and extended roof life, Ag panels are a great choice for roofing projects. These low rib, sleek looking panels are an economical decision for your building.




Ag Panel Size



Product Specifications

- Available in 29ga .014 AZ35 Liner Panel
- Available in 29ga .014 AZ35 40yr Select Panel
- Available in 29ga .0153 AZ50 40yr Premium Panel
- Available in Weather XL and Weather AL Crinkle Finish
- Application: Roof and Wall
- Coverage Width: 36"
- Panel Attachment: Exposed Fastener System
- Minimum Slope: 3:12
- Rib Height: 0.75"
- Rib Spacing: 9" on Center
- Available in AZ35 Galvalume
- Available in AZ50 Galvalume
- Available in G100 Galvanized

AG PANEL TRIMS





Ag Panel Trim

6" CORNER 	4" MINI CORNER 	UPPER GAMBREL 	LOWER GAMBREL
LG RESIDENTAL RAKE 	SM RESIDENTAL RAKE 	3-1/2" FACIA 	5-1/2" FACIA
7-1/2" FACIA 	DRIP EDGE 	MINI GUTTER APRON 	GUTTER APRON
END WALL 	SIDE WALL 	3-1/2" POST TRIM 	5-1/2" POST TRIM
7-1/2" POST TRIM 	DOUBLE ANGLE 	RAT GUARD 	SQUARE BASE



Ag Panel Trim

6" RIDGE CAP 	8" RIDGE CAP 	10" RIDGE CAP 	VALLEY
SLIDING DOOR JAMB 	SNOW GUARD 	J TRIM 	SQUARE TRACK COVER
ROUND TRACK COVER 	OVERHEAD DOOR J FINISHER 	OVERHEAD DOOR DRIP FINISHER 	DOUBLE J
F & J 	UPPER MOUNT F 	LOWER MOUNT F 	WINDOW DRIP CAP
SQUARE POST WRAP 	PROFILED POST WRAP 		


PBR PANEL

CMS PBR Panel

Exposed Fastener System

PBR-Panel is a multi-use wall and roof panel used primarily in pre-engineered metal building applications. PBR-Panel is also a popular choice for commercial metal roofing. The PBR-panel is low maintenance, durable metal roofing alternative to conventional roofing. Choose from many designer colors for a sleek, attractive appearance.



PBR Panel Size



Product Specifications

- Available in 26ga .0185 AZ50 Premium Panel
- Available in Sherwin Williams Weather XL finish
- Coverage 36"
- Rib Height: 1.25"
- Applications: Roof and Walls
- Minimum Slope: 1 1/2:12
- Panel Attachment: Exposed Fastener System
- Rib Spacing: 12" on Center
- Available in AZ50 Galvalume Substrate


PBR PANEL TRIMS






PBR Panel Trim


COMMERCIAL RIDGE CAP




PBR PANEL FORMED RIDGE




COMMERCIAL RAKE




COMMERCIAL HIGH SIDE EAVE




COMMERCIAL SNOWGUARD




COMMERCIAL POST HUNG GUTTER




COMMERCIAL PRE HUNG GUTTER




COMMERCIAL JAMES POST HUNG




COMMERCIAL JAMES ST PRE HUNG GUTTER




COMMERCIAL JAMES ST RAKE




COMMERCIAL JAMES ST H.S.E.




COMMERCIAL LOWER GAMBREL




COMMERCIAL END WALL




COMMERCIAL SIDEWALL




COMMERCIAL VALLEY




COMMERCIAL UPPER GAMBREL




COMMERCIAL OUTSIDE CORNER




COMMERCIAL INSIDE CORNER



COMMERCIAL WINDOW DRIP



COMMERCIAL GUTTER APRON







PBR Panel Trim




COMMERCIAL RAT GUARD




COMMERCIAL J TRIM




COMMERCIAL DOUBLE J




COMMERCIAL F & J




COMMERCIAL RESIDENTAL RAKE




COMMERCIAL DOUBLE ANGLE



PBR PANEL GUTTER HANGER




COMMERCIAL HIGH SIDE



Specify Pitch

COMMERCIAL VALLEY COVER




FF100 Standing Seam

FF100 Standing Seam Panel

One of the most durable, weatherproof roofing systems available. This type of panel has a sleek and modern look as well as a weather-tight material. CMS FF100 Standing Seam panels gives you a beautiful roof without a single screw showing. Extra protection from leaks is one of the many benefits of our FF100 Standing Seam panel. Our panels are designed to withstand the most rigorous weather condition.

FF100 Standing Seam Panel Size



Product Specifications

- Available in 26ga .0185 Panel Thickness
- Available in Weather XL and Weather XL Crinkle Finish 40yr paint
- Fasteners Hidden from Elements
- Rib Height: 1"
- Best Leak Prevention
- 1.0 mil Paint Thickness
- Advance Rust Blocking
- Advance Dent Resistance
- Applications: Roof
- Coverage Widths: up to 16"
- Minimum Slope: 1 1/2:12
- Panel Attachment: Snaplock overlap with Fastener Flange System
- Available in AZ50 Galvalume Substrate

FF100 Standing Seam







FF100 Snaplock

Concealed Fastner Trims


FF100 RAKE




FF100 CHOICE RAKE




FF100 END WALL




FF100 SIDEWALL




FF100 UPPER GAMBREL




FF100 LOWER GAMBREL




FF100 DRIP EDGE




FF100 VENT RIDGE CAP




FF100 RIDGE CAP




FF100 VALLEY




FF100 WIDE VALLEY




FF100 VALLEY CLEAT




FF100 HIGH SIDE EAVE




FF100 CHOICE HIGH SIDE EAVE




FF100 CHOICE HIGH SIDE EAVE CLEAT




FF100 CHOICE RAKE CLEAT




FF100 Z CLEAT




FF100 VENTED J CLEAT



FF100 STANDARD J CLEAT



FF100 DEEP J CLEAT






FF100 Snaplock

Concealed Fastner Trims

COLORED RIVETS




COLOR SEALANTS



PAN HEADED SCREWS



BUTYLE TYPE




TOUCH UP PAINT



FOLDING TOOL



SNOW TRAX



SNOW DEFENDER




SNAP Z 1000TM



FF150 Standing Seam

FF150 Standing Seam Panel



One of the most durable, weatherproof roofing systems available. This type of panel has a sleek and modern look as well as a weather-tight material. CMS FF150 Standing Seam panels gives you a beautiful roof without a single screw showing. Extra protection from leaks is one of the many benefits of our FF150 Standing Seam panel. Our panels are designed to withstand the most rigorous weather condition.



Product Specifications

- Available in 26ga .0185 panel thickness
- Available in Weather XL and Weather XL Crinkle Finish 40yr Paint
- Fasteners Hidden from Elements
- Rib Height: 1-1/2"
- Best Leak Prevention
- Advance Rust Blocking
- Advance Dent Resistance
- Applications: Roof
- Coverage Widths: up to 15"
- Minimum Slope: 1 1/2:12
- Panel Attachment: Snaplock overlap with Fastener Flange System
- Available in AZ50 Galvalume Substrate

FF150 Standing Seam





FF150 Snaplock

Concealed Fastner Trims


FF150 RAKE 	FF150 CHOICE RAKE 	F150 END WALL 	FF150 SIDEWALL
FF150 UPPER GAMBREL 	FF150 LOWER GAMBREL 	FF150 DRIP EDGE 	FF150 VENT RIDGE CAP
FF150 RIDGE CAP 	FF150 VALLEY 	FF150 WIDE VALLEY 	FF150 VALLEY CLEAT
FF150 HIGH SIDE EAVE 	FF150 CHOICE HIGH SIDE EAVE 	FF150 CHOICE HIGH SIDE EAVE CLEAT 	FF150 CHOICE RAKE CLEAT
FF150 Z CLEAT 	FF150 VENTED J CLEAT 	FF150 STANDARD J CLEAT 	FF150 DEEP J CLEAT



FF150 Snaplock

Concealed Fastner Trims

COLORED RIVETS




COLOR SEALANTS



PAN HEADED SCREWS



BUTYLE TYPE



TOUCH UP PAINT



FOLDING TOOL



SNOW TRAX




SNOW DEFENDER



SNAP Z 1500TM




SNOW RAIL



SS200 Standing Seam

SS200 Standing Seam Panel


One of the most durable, weatherproof roofing systems available. This type of panel has a sleek and modern look as well as a weather-tight material. CMS SS200 Standing Seam panels gives you a beautiful roof without a single screw showing. Extra protection from leaks is one of the many benefits of our SS200 Standing Seam panel. Our panels are designed to withstand the most rigorous weather condition.



Product Specifications

- Available in 26ga .0185 panel thickness
- Available in 24ga .0239 panel thickness
- Available in Weather XL and Weather XL Crinkle Finish 40yr Paint
- Fasteners Hidden from Elements
- Rib Height: 2"
- Best Leak Prevention
- 1.0 mil Paint Thickness
- Advance Rust Blocking
- Advance Dent Resistance
- Coverage Widths: 14-1/2"
- Minimum Slope: 1:12 pitch
- Panel Attachment: Mechanical Seam Overlap with Fastener Clip System
- Available in AZ50 Galvalume Substrate
- Butyle tape required for sealing seams
- Application: Roof

SS200 Standing Seam







SS200 Mech. Seam

Concealed Fastner Trims


SS200 RAKE




SS200 CHOICE RAKE




SS200 HIGH SIDE EAVE




FF150 CHOICE HIGH SIDE EAVE




SS200 RIDGE CAP




SS200 HIP CAP




SS200 END WALL



SS200 SIDE WALL




SS200 DRIP EDGE




Also make it in 90*


SS200 VALLEY




SS200 Z CLEAT




SS200 J CLEAT




SS200 DEEP J CLEAT




SS200 CHOICE RAKE CLEAT




SS200 CHOICE HIGH SIDE EAVE CLEAT




SS200 VALLEY CLEAT




SS200 JAMES ST HIGH SIDE EAVE




SS200 JAMES ST RAKE



SS200 JAMES ST GUTTER POST HUNG



SS200 JAMES ST GUTTER PRE HUNG






SS200 Mech. Seam

Concealed Fastner Trims




SS200 JAMES ST
GUTTER HANGER



SNAP Z 2000TM VENTED
RIDGE CLOSER



SNOW RAIL




SNOW DEFENDER 1500



PAN HEADED SCREWS




COLORLED RIVETS



COLOR SEALANTS



BUTYLE TYPE



TOUCH UP PAINT




FOLDING TOOL



FLOATING CLIP



FIXED CLIP




Board & Batten

Board & Batten Panel

Our Board & Batten panel is not only a stylish choice but a cost-effective choice. This type of panel is fade resistant and low maintenance. CMS Board and Batten exterior siding can last for many years-even decades- if properly maintained. It has minimal exposed fasteners. Weather is never an issue with this type of panel. Board and Batten siding can be installed vertically for a one-of-a-kind appearance. Even better, our board and batten siding is available in a variety of colors to match your desired aesthetic.


Board & Batten Panel Size



Product Specifications

- Available in 26ga .0185
- Available in Weather XL and Weather XL Crinkle Finish 40yr Paint
- Fasteners Hidden from Elements
- Rib Height: 3/4"
- Batten Width: 2"
- 1.0 mil Paint Thickness
- Advance Rust Blocking
- Advance Dent Resistance
- Applications: Walls and Ceilings
- Coverage Widths: 10-1/2 " up to 16"
- Panel Attachment: Hook & Slot overlap with Fastener Flange System
- Available in AZ50 Galvalume Substrate

Board & Batten





Board & Batten

Exposed Fastner Trims



6" B&B CORNER 	B&B RAT GUARD 	B&B J TRIM 	B&B SQUARE BASE
B&B WINDOW DRIP 	B&B DOUBLE ANGLE 	B&B DEAD END TRIM 	B&B J CLEAT
B&B TRANSITIONAL TRIM 	B&B CORNER TRIM 	B&B Z CLEAT 	B&B INSIDE CORNER



Use in conjunction
with J Cleats & Z Cleats



Accessories





Accessories


Pipe Boots

Low Temp Pipe Boot

Universal Roof boot Round Flexible Sleeve

The Proven Choice with a 20-year warranty.

- Easy, on-site customization for superior fit
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction
- Maximum resistance to ozone weathering



Black & Gray

Ozone Resistance	70= @ 500pphm (EPDM and RS)
Ozone Resistance	25% (EPDM), 50% (RS)
Low Temp Resistance	+55*/+67°F (EPDM), +74°C/+101°F (RS)

High Temp Pipe Boot

Universal Roof boot Round Flexible Sleeve

The Proven Choice with a 20-year warranty.

- Easy, on-site customization for superior fit
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction
- Maximum resistance to ozone weathering



Red & Gray

Ozone Resistance	70= @ 500pphm (EPDM and RS)
High Temp Resistance	Intermittent: +135°C/+275°F (EPDM), +260°C/+500°F (RS) Continuous: +100°C/+212°F (EPDM), +225°C/+437°F (RS)
Ozone Resistance	25% (EPDM), 50% (RS)

Retrofit Pipe Boot

Round Flexible Sleeve

The Proven Choice with a 20-year warranty.

- Easy, on-site customization for superior fit
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction
- Maximum resistance to ozone weathering



Ozone Resistance	70= @ 500pphm (EPDM and RS)
Ozone Resistance	25% (EPDM), 50% (RS)
Low Temp Resistance	+55*/+67°F (EPDM), +74°C/+101°F (RS)


Pipe Range	Mini 0"- 3/4"	#1 1/4"-2-1/2"	#2 1-3/4"-3"	#3 1-1/5"-5"	#4 3"-6-1/4"	#5 4-1/4"-7-3/4"	#6 5"-9"	#7 6"-11"	#8 7"-13"	#9 9"-19"
Base	4" (101mm)	3-1/4" (82mm)	6-1/4" (158mm)	7-3/4" (196mm)	9-1/4" (234mm)	10-1/2" (266mm)	13" (330mm)	14-1/2" (368mm)	16-1/2" (412mm)	25-1/4" (641mm)



Accessories

Sealant

Butyl Tape



- Trimmable joints and end lap sealing tape
- Non-staining, permanently flexible
- Seals around windows, doors, roof vents, and more
- Roll won't telescope from heat before installation
- Keeps even hot metal roofing panels in place no melting or oozing
- Made in the USA
- Economical
- 40 Year limited warranty

This versatile, trimmable, end-lap dealing tape joins metal to metal, and seals around windows, doors, roof vents, stacks, access doors and other penetration points. non-staining and permanently flexible, mastix stays in place with no melting or oozing, even in extreme heat.

Color	Off-white to gray
Solubility in water	Insoluble
Size	3/32"x3/8"x45' or 3/32"x 1"x45' or 3/32"x2.5"x 45'
Reactivity Hazard	0-Minimal
Flammability	0-Minimal
Chemical Name	Isobutylene
Appearance	Soft, pliable gum

Emseal



- Expands from 1/4" to 1"
- Follows, flexes, expands, compresses to fit
- UV stable
- Universally adaptable to most roof panels, including hips and valleys
- Highly resistant to bugs and vermin
- Maintains seal in heat and cold
- Will not leech out or stain
- Economical
- 40 year limited warranty

Emseal expands from 1/4" to 1" allowing it to fill any shaped gap in the construction of metal buildings, doors and windows, concrete, wood and more. It is adaptable to most roof panels, including hips and valleys. Highly resistant to bugs and vermin, Emseal maintains it's seal in heat and cold and will not leach out or stain.

Color	Base foam is black, other colors available
Density	10lbs./cu Ft. (150kg/m3)
Thermal Conductivity	12, 106 BTU (hr.) (ft2) (*F/ft)
Temp Stability Range	-25°F to 212°F
Flammability	UL 94 HF1, Self-extinguishing, DIN 4102, B1 Compression @ 50%, B2 Compressed
Weather Resistance	Excellent
Compression Set	Maximum 2%
Tensile Strength	21.8 psi
Manufacturer's Lab	-40°C to 120°C



Accessories

Closure Foam/Vented Ridge

Custom fit foam closure system



AG PANEL OUTSIDE



R PANEL OUTSIDE



AG PANEL INSIDE



R PANEL INSIDE

Closure-Foam comes in 2 standard profiles to match the rib pattern of Ag Panel & R Panel. Outside Closure is designed to seal on the outside of the panel and Inside Closure is designed to seal underneath the panel. It is Designed to stay put, industrial adhesive eliminates blow away problems with a 1/4" adhesive bead applied to either the flat or the ribbed side of Closure-Foam. It even adheres in subfreezing temperatures and on wet surfaces. Closure-Foam is economically priced without sacrificing quality.

- Full 1/4" bead of adhesive.
- Excellent UV resistance/long lasting seal.
- no excess scrap for easier cleanup.
- holds up to -25°F.
- Easy Application

Low Profile Ridge Vent



VENTED RIDGE CLOSURE

Our Vented Ridge Closure strip includes Python polyester vent material inserts for a snug fit and optimum ventilation at a cost lower than traditional fans and louvers. Made with recycled materials, it features a 40-yr warranty and proprietary adhesive for a superior net-free ventilation that reduces condensation and helps lower utility costs. This durable, modified polyester is a non-woven, non-wicking, fiber-based matting. Its specially cut contours provides a custom, low-profile fit for any pitch and is available in AG Panel & R panel profiles. Vented Ridge Closure provides a superior net-free ventilation area that helps keep out moisture, pests and dust. Plus, it can be installed by just one person in two easy steps.

- Lower, custom fit profile
- Custom-cut profiles for snug fit
- Helps reduce utility cost.
- Moisture and pest barrier
- Easy to installation
- Non-obstructive appearance
- Superior net-free ventilation reduced condensation

Universal Smart Vent



UNIVERSAL SMART VENT


- Fits multiple profiles
- Helps reduce utility cost.
- Moisture and pest barrier
- Easy to install
- Non-obstructive appearance
- Superior net-free ventilation reduced condensation



Accessories

Vented Ridge

9-12" Throat Ventilator




9-12" Throat Commercial Ventilator

- 10' Long Ventilator
- 1/2" Galvanized Mesh
- All Exposed Edges Hemmed
- Rain Diverter (metal)
- Continuous Draining Space
- 2" Nailing Flange
- Idea; for large Attic or Entire Building Ventilation such as Warehouses and Industrial Buildings

Dimensions

Throat	A	B	C	D	E
9"	13"	21-1/4"	14-1/2"	16"	28-1/4"
12"	17"	28-1/2"	18"	20-3/4"	33"

3.5" Throat Ridge Vent



RV35 Ridge-Vent

10' long low profile ventilator

- 1/2" Galvanized Mesh
- All Exposed Edges Hemmed
- Rain Diverter (Metal)
- Continuous Drainage Space
- 2" Nailing Flange Ideal for large attic or entire building ventilation such as horse, cattle or poultry buildings
- 3-1/2" unrestricted throat with 36 sq. inches of free area per lineal foot
- 13-1/4" overall coverage, with wider flanges available
- Use in conjunction with an equal area of vented soffit material or louvers for maximum air flow (36 sq in per lineal foot, 2.5 sq ft per vent)



Accessories



Polycarbonate Panel

Available in:

- 12' R Panel Profile Clear
- 12' R Panel Profile White
- 12' Ag Panel Profile Clear
- 12' Ag Panel Profile White

EXCELLENT LIGHT TRANSMISSION

- PROVIDES FREE NATURAL LIGHT ENERGY
- MORE PRODUCTIVE LIVESTOCK
- REDUCES RUNNING COSTS OF BUILDING
- DAMAGE & IMPACT RESISTANT
- 200 TIMES STRONGER THAN GLASS
- HIGH OPTICAL CLARITY
- PERFORMS WELL IN EXTREME TEMPS
- CHEMICAL RESISTANT
- LIGHTWEIGHT, EASILY HANDLED & INSTALLED
- EXCELLENT FIRE PERFORMANCE
- LONG LASTING UV PROTECTION
- 10-YEAR LIGHT TRANSMISSION
- 3-YEAR WEATHER BREAKAGE WARRANTY



Roof Sealant

- Paintable, Full UV protection
- Skins in 1 hour
- 4 Season application
- Mold and Mildew resistant
- Cures to a tough flexible bead
- Field proven for over 30 years
- Max Coverage: 14 linear feet
- 10 Ounce tubes
- Single tube or Carton of 12



The NPC Sealants Solar Seal #900 is a terpolymer rubber adhesive and sealant. It is a high performance colored alternative to any silicone or urethane chemistry. This sealant by NPC Sealants is manufactured for commercial and high end residential jobs. Solar Seal 900 is formulated to work for materials such as vinyl, fiber-cement siding, fiberglass, cedar, metal roofing and panels, brick, masonry, sky lights, sun rooms, truck trailers, termination bars, clay tiles, copper, curtain walls, cured concrete, and flashing.



Accessories

Fasteners

Metal to Wood



3/4" Stitch



1" High Low



1.5" High Low



2" High Low



3" High Low

- Type-17 26-degree sharp point
- Bonded sealing washer

- High major thread with low minor thread
- 1/4" hex head

Metal to Metal



7/8" Stitch



1.25" self-driller



2" self-driller

- Self-drilling Tip
- Bonded sealing washer
- 5/16" Hex head

Miscellanea



1" Pan Head
Self-driller



1" Pan Head
wood screw



1.5" Pan Head
Self-driller



3" Decking
screw



pop rivets



Accessories

Cupolas



Cupola Sizes:

- 2x2
- 3x3
- 4x4
- 6x6

Window Options

- White
- Black

Specify pitch of roof

Specify colors

- Base
- Sides
- Roof

Louvered sides or windowed sides

Peel and Stick Ice and Water



Specs

- Roll Size: 36"x67'
- Roll Weight: 55 lbs



Benefits:

- Easy to handle
- Skid-resistant polymer coating and proprietary Fiber Claw walking surface dynamic steep slope traction.
- Stronger than type 15 or 30 felt
- Lighter than type 15 or 30 felt
- Won't buckle, warp, or crack: superior lay-flat properties and water resistance keeps HydraShell Premium Ice and Water from warping, wrinkling, and cracking in cold weather.
- Warranty: Lifetime limited warranty.



Accessories

HydraShell Premium Underlayment



Roll Size

- 48"x250'




Hydra Shell underlayment is among the safest, strongest and best-performing underlayment's on the market. Woven of heavyweight polymer fabric, Premium underlayment offers superior strength and durability, steep-slope traction, water resistant, a wrinkle free surface, and resistance to UV breakdown. The textured woven fabric surface offers dynamic traction and is ideal for steep slopes in a variety of weather conditions. Hydra Shell Premium is rated for commercial and residential applications using plastic caps and roofing nails (3/8" head), and is ideal for roof underlayment for metal, tile, slate and variety of other sloped roofing.

Features and Benefits:

- **Safer:** Skid-resistant polymer coating and proprietary Fiber Claw™ walking surface offers dynamic steep slope traction.
- **Stronger** than Type 15 or 30 felt and easier to handle during installation.
- **Lighter** than Type 15 or 30 felt and easier to handle during installation.
- **Won't buckle, warp, or crack:** Superior lay-flat properties and water resistance keeps HydraShell™ Premium from warping, wrinkling, and cracking in cold weather.
- **Easy to apply**
- **Warranty:** Lifetime limited warranty applies to HydraShell™ Premium.

Single Bubble Metal Insulation



Roll Size

- 6'X125'



Benefits:

- **Blocks Radiant Heat Transfer.**
- **Prevents Interior Condensation**
- **Unaffected by Humidity**
- **Will not Mold or Mildew**
- **Easy to handle and Install**
- **Safe, non-toxic and non-carcinogenic**
- **UV Resistant**



Accessories

Standing Seam Backer Rod

Standing Seam backer Rod is a flexible, extruded closed cell foam product that is 5/8" diameter and comes with adhesive backing. Many installers use backer rod to help prevent oil canning of non-striated standing seam metal roof panels. Our Standing Seam backer rod is an innovative product that comes with an adhesive backing for saving a time saving way to apply backer rod to the panels. Backer Rod can be easily trimmed to the precise size needed for upcoming Standing Seam Projects.



Roll Size

- 1500' length


Features and Benefits:

- Relieves internal stresses and waviness
- Easy to install
- Helps minimize Oil Canning
- Closed-cell Foam

Box Gutter Expansion Joint

Features and Benefits:

- Expandable edge strips flashing in grey
- flashes hi-rib and standing-seam profiles
- stretch and form to fit and seal
- Flash between dissimilar materials
- Ideal for square ducts, chimneys, skylights
- 20-year warranty



Roll Size

- 9" wide X 12', 33' and 50' length



Color Chart



Color Chart


Smooth Paint Colors

Bright White	Alamo White	Light Stone	Ivory
Ash Gray	Tan	Taupe	Burnished Slate
Pewter Gray	Charcoal	Brown	Copper
Ocean Blue	Gallery Blue	Hunter Green	Dark Green
Crimson Red	Rustic Red	Burgandy	Galvalume
Matte Black	Shiny Black		




Color Chart


Textured Paint Colors




Textured White




Textured Light Stone




Textured Ash Gray




Textured Taupe




Textured Brown




Textured Charcoal




Textured Burnished Slate




Textured Black




Textured Red




Textured Rust



Textured Burgandy



Textured Green



Textured Blue



**SHERWIN
WILLIAMS®**

WeatherXL™

Color Chart

Paint Color Chart

● Special Order ● Available Now

*TX	Textured	AG Panel			PBR	SS
<u>SS</u>	Standing Seam	29 Ga. .015 <u>P</u> 40 YR.	29 Ga. .014 30 YR.	29 Ga. .015 <u>G100</u>	26 Ga. .018	26 Ga. .018 <u>SS</u>
<u>P</u>	Premium					
	Brilliant White	●	●	●	●	●
	Alamo	●		●	●	●
	Ash Gray	●	●	●	●	●
	Pewter Gray	●		●		●
	Charcoal	●	●	●	●	●
	Ivory	●		●		●
	Light Stone	●	●	●	●	●
	Tan	●	●	●	●	●
	Taupe	●	●	●	●	●
	Brown	●	●	●	●	●
	Burnished Slate	●	●	●	●	●
	Crimson Red	●	●	●	●	●
	Rustic Red	●	●	●	●	●
	Burgandy	●	●	●	●	●
	Ocean Blue	●		●	●	●
	Gallery Blue	●	●	●	●	●
	Hunter Green	●		●	●	●
	Dark Green	●	●	●	●	●
	Shiny Black	●	●	●	●	●
	Black	●	●	●		●
	Copper	●		●	●	●
	Bare Acrylic	●				●
	White *TX	●				●
	Light Stone *TX	●				●
	Ash Gray *TX	●				●
	Taupe *TX	●				●
	Brown *TX	●				●
	Charcoal *TX	●				●
	Black *TX	●				●
	Burnished Slate *TX	●				●
	Red *TX	●				●
	Rust *TX	●				●
	Burgandy *TX	●				●
	Green *TX	●				●
	Blue *TX	●				●



About Us





About Us

Our Company Value

Service:

We are committed to delivering what you need, when you need it.

Quality:

We Believe you deserve the best; therefore, we provide High-quality metal product that ensure solid results.

Value:

It's not just about making the sale for us, it's about making your project, whatever it is, come true.






About Us


Our Promise to You

We make metal easy. We're here for you. We know what you need and what you expect, and we will deliver top quality Customer Service and Professional value, with a product that will satisfy, and a team that makes sure you get what you need, when you need it.



Our Service Area

We Service Iowa, Illinois, Missouri, Wisconsin, Minnesota and Nebraska



YEAR 2025