



SUPPLY CATALOG

www.championmetalsupply.com



We are a family-owned manufacturer and distributor dedicated to making metal easy for contractors, builders, and homeowners across the Midwest and South. Located in Riverside, Iowa, we bring more than 15 years of on-the-job metal roofing and siding experience to every order, delivering the high-quality products, dependable service, and professional support our customers expect. Our mission is simple: provide fast, convenient service, exceptional craftsmanship, and real value that helps make every project a success. Because just like your building, what we do isn't defined by individual parts—it's how we put them together. At Champion Metal Supply, we're committed to giving you the right materials, the right service standards, and the right solutions to ensure you get what you need, when you need it.



26 G
Light Stone

TAN
ZINC TRIM

ALUMINUM
ZINC TRIM

LIGHT STONE
ZINC TRIM

ZINC TRIM

TAN

300 L

200 T

ALUMINUM

300 L

200 T

LIGHT STONE

340 L

253 T

PLASTER GREEN

333 L

153 T

GALVALUME


140 L

153 T



Champion Transport was created with one purpose in mind—to give our customers a better, faster, more reliable delivery experience. Instead of relying on third-party scheduling delays, we built our own logistics team and fleet, allowing us to deliver products on your timeline, not someone else's. No more waiting weeks or even a month for material to arrive. Whether it's a small residential order or a massive commercial project, our dedicated drivers and full fleet of vehicles ensure your metal gets from our facility to your job site quickly, efficiently, and with the level of service you expect from Champion Metal Supply.





CMS Iowa


2527 Highway 22
Riverside, IA
(319) 331-1618

CMS Texas

100 Ferguson Dr,
Corsicana, TX
(254) 405-7284


Exposed Fastener System

(Ag Panel & PBR Panel)



Concealed Fastener Systems

(Standing Seam & Board and Batten)







AG Panel

Applications: Roof & Walls

Coverage Width: 36"

Minimum Slope: 3:12

Panel Attachment: Exposed Fastener System

Rib Height: 0.75"

Rib Spacing: 9" on center

Length: Custom cut-to-length

Gauges:

29ga – .014 AZ35 Liner Panel

29ga – .014 AZ50 40-Year Select Panel


29ga – .0153 AZ50 40-Year Premium Panel

Coatings:

Weather XL, Weather XL Crinkle

Available Substrates:

AZ50 Galvalume, G100 Galvanized



SHERWIN-WILLIAMS.
Coil Coatings

WeatherXL

Ag Panel | Trim Options

EXPOSED FASTENER SYSTEM

3.5" Facia	5.5" Facia	7.5" Facia	6" Corner	4" Mini Corner	Gutter Apron
Mini Gutter Apron	3.5" Post Trim	5.5" Post Trim	7.5" Post Trim	Square Base	Double Angle
Square Post Wrap	Profiled Post Wrap	Side Wall	End Wall	Rat Guard	J Trim
Double J	Overhead Door J-Finisher	F & J Combo	Square Track Cover	Sm. Round Track Cover	Lg. Round Track Cover
Overhead Door Drip Finisher	Lg. Residential Rake	Sm. Residential Rake	Upper Gambrel	Lower Gambrel	Snow Guard
Upper Mount F	Lower Mount F	Drip Edge	Sliding Door Jam	Valley	Window Drip Cap
6" Ridge Cap	8" Ridge Cap	10" Ridge Cap			



PBR Panel

PBR-Panel is a multi-use wall and roof panel used primarily in pre-engineered metal building applications. The PBR Panel is a low-maintenance, durable metal roofing alternative to conventional roofing.

Coverage Width: 36"

Minimum Slope: 1/2:12

Panel Attachment: Exposed Fastener System

Rib Height: 1.25"

Rib Spacing: 12" on center

Length: Custom cut-to-length

Gauges:


26ga – .0185 AZ50 Premium Panel

Coatings:

Weather XL Crinkle 40-Year Paint

Available Substrates:

AZ50 Galvalume, G90 Galvalume

































SHERWIN-WILLIAMS
Coat Coatings

WeatherXL

PBR Panel | Trim Options

EXPOSED FASTENER SYSTEM

Comm. Ridge Cap	Formed Ridge	Comm. Valley	Comm. Valley Cover	Comm. J Trim
				
Comm. Double J	Comm. F & J	Comm. End Wall	Comm. Sidewall	Comm. Window Drip
				
Comm. Upper Gambrel	Comm. Lower Gambrel	Comm. Rake	Comm. James St. Rake	Comm. Residential Rake
				
Comm. Post-Hung Gutter	Comm. Pre-Hung Gutter	James St. Pre-Hung Gutter	James St. Post-Hung Gutter	PBR Panel Gutter Hanger
				
Comm. Gutter Apron	Comm. Outside Corner	Comm. Inside Cover	Double Angle	Com. Rat Guard
				
Comm. High Side Eave	Comm. James St. H.S.E.	Comm. High Side	Comm. Snowguard	
				



FF100

Applications: Roof

Coverage Width: 16"

Minimum Slope: 1.5:12

Panel Attachment:

Snaplock overlap with fastener flange system

Hidden fasteners

Rib Height: 1"

Length: Custom cut-to-length

Gauges:

26ga – .0185 panel thickness


Coatings:

Weather XL 40-Year Paint Finish

Weather XL Crinkle 40-Year Paint Finish

Available Substrates:

AZ50 Galvalume






SHERWIN-WILLIAMS.
Coil Coatings

WeatherXL

FF100 | Trim Options

STANDING SEAM





FF150

Applications: Roof

Coverage Width: 15"

Minimum Slope: 1.5:12

Panel Attachment:

Snaptopk overlap with fastener flange system

Hidden fasteners

Rib Height: 1.5"

Length: Custom cut-to-length

Gauges: 26ga – .0185 panel thickness

Coatings:

Weather XL 40-Year Paint Finish

Weather XL Crinkle 40-Year Paint Finish





















Available Substrates:

AZ50 Galvalume



SHERWIN-WILLIAMS.
Coil Coatings

WeatherXL™

FF150 Rake 	FF150 Choice Rake 	FF150 Choice Rake Cleat 	FF150 Z Cleat 	FF150 Vented J Cleat 
FF150 Standard J Cleat 	FF150 Deep J Cleat 	FF150 High Side Eave 	FF150 Choice High Side Eave 	FF150 Choice High Side Eave Cleat 
FF150 End Wall 	FF150 Side Wall 	FF150 Upper Gambrel 	FF150 Lower Gambrel 	FF150 Drip Edge 
FF150 Ridge Cap 	FF150 Vent Ridge Cap 	FF150 Valley 	FF150 Wide Valley 	FF150 Valley Cleat 



SS200

Applications: Roof

Coverage Width: 14.5"

Minimum Slope: 1:12

Panel Attachment:

Mechanical seam overlap with fastener clip system

Hidden fasteners

Butyl tape required for seam sealing

Rib Height: 2"

Gauges:

26ga — .0185 panel thickness

24ga — .0239 panel thickness



Coatings:

Weather XL 40-Year Paint Finish

Weather XL Crinkle 40-Year Paint Finish

Available Substrates:

AZ50 Galvalume





SHERWIN-WILLIAMS.
Coil Coatings

WeatherXL

SS200 | Trim Options

STANDING SEAM





Board & Batten

Applications: Walls & Ceilings

Coverage Width: 10" to 16"

Minimum Slope: 3:12

Panel Attachment: Concealed Fastener System

Rib Height: 0.75"

Rib Spacing: 9" on center

Length: Custom cut-to-length

Gauges:

26ga – .0185

Coatings:

Weather XL 40-Year Paint Finish

Weather XL Crinkle 40-Year Paint Finish

Available Substrates:

AZ50 Galvalume
















SHERWIN-WILLIAMS.
Coil Coatings

WeatherXL

Board & Batten | Trim Options

BOARD & BATTEN

BB 6" Corner 	BB Corner Trim* 	BB Inside Corner 	BB Inside Corner Cleat* 	BB Double Angle 
BB J Cleat 	BB Z Cleat 	BB Square Base 	BB Dead End 	BB Rat Guard 
BB Transitional Trim* 	BB Window Drip 	BB J Trim 	* Use in conjunction with J Cleats & Z Cleats	



Pipe Boots Low Temp

- The Proven Choice with a 20-year warranty.
- Easy, on-site customization for superior fit.
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction.
- Maximum resistance to ozone weathering.

Ozone Resistance	70= @ 500pphm (EPDM and RS)
Ozone Resistance	25% (EPDM), 50% (RS)
Low-Temp Resistance	+55°C /+67°F (EPDM), +74°C /+101°F (RS)



Retrofit Pipe Boots

- The Proven Choice with a 20-year warranty.
- Easy, on-site customization for superior fit.
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction.
- Maximum resistance to ozone weathering.

Ozone Resistance	70= @ 500pphm (EPDM and RS)
Ozone Resistance	25% (EPDM), 50% (RS)
Low-Temp Resistance	+55°C / +67°F (EPDM), +74°C / +101°F (RS)

Pipe Range	Mini	#1	#2	#3	#4	#5	#6	#7	#8	#9
	0"- 3/4"	1/4"- 2 1/2"	1 3/4"- 3"	1 1/5"- 5"	3"- 6 1/4"	4 1/4"- 7 3/4"	5"- 9"	6"- 11"	7"- 13"	9"- 19"
Base	4" (101 mm)	3 1/4" (82 mm)	6 1/4" (158 mm)	7 3/4" (196 mm)	9 1/4" (234 mm)	10 1/2" (266 mm)	13" (330 mm)	14 1/2" (368 mm)	16 1/2" (412 mm)	25 1/4" (641 mm)



Pipe Boots High Temp

- The Proven Choice with a 20-year warranty.
- Easy, on-site customization for superior fit.
- Sleeve flexibility absorbs vibration and pipe movement causes by expansion/contraction.
- Maximum resistance to ozone weathering.

Ozone Resistance	70= @ 500pphm (EPDM and RS)
Ozone Resistance	25% (EPDM), 50% (RS)
Intermittent High-Temp Resistance	+135°C / +275°F (EPDM), +260°C / +500°F (RS)
Continuous High-Temp Resistance	+100°C / +212°F (EPDM), +225°C / +437°F (RS)



#900 SOLAR SEAL®

Powered by advanced Terpolymer Technology, offering a superior alternative to traditional silicone and urethane sealants. Engineered for commercial, industrial, and high-end residential applications, it provides exceptional protection, flexibility, and long-term performance—making it one of the most reliable sealants in its class.

Available in all NPC Standard Colors, as well as premium and custom color options, in 10.3 oz consumer or 19 oz pro-size cartridges

- Built on Terpolymer Technology—the best protector and an alternative to silicone & urethane chemistry
- Exceptional adhesion and joint flexibility
- Full UV protection
- Paintable
- Skins in 1 hour
- Four-season application





Butyl Tape

This versatile, trimmable, end-lap dealing tape joins metal to metal, and seals around windows, doors, roof vents, stacks, access doors and other penetration points. non-staining and permanently flexible, mastix stays in place with no melting or oozing, even in extreme heat.

40-year limited warranty

Size: $3/32''$ x $3/8''$ x 45'

Available in: $3/8''$, $1/2''$, $1''$, or $2''$



Emseal

Emseal expands from $1/4''$ to $1''$ allowing it to fill any shaped gap in the construction of metal buildings, doors and windows, concrete, wood and more. It is adaptable to most roof panels, including hips and valleys. Highly resistant to bugs and vermin, Emseal maintains its seal heat and cold and will not leach out or stain.

40 year limited warranty.

Color: Base foam is black (other colors available)

Density: 10 lbs./cu ft. (150kg/m³)

Flammability: UL 94 HF1, self-extinguishing, DIN 4102, B1 compression at 50%, B2 compressed


Temperature Stability Range: -25°F to 212°F



Insulation

- Blocks Radiant Heat Transfer.
- Prevents Interior Condensation
- Unaffected by Humidity
- Will not Mold or Mildew
- Easy to handle and Install
- Safe, non-toxic and non-carcinogenic
- UV Resistant

Roll Size: 6' x 125'



Closure Foam

Closure-Foam comes in 2 standard profiles to match the rib pattern of Ag Panel & R Panel. Outside Closure is designed to seal on the outside of the panel and Inside Closure is designed to seal underneath the panel. It is Designed to stay put, industrial adhesive eliminates blow away problems with a 1/4" adhesive bead applied to either the flat or the ribbed side of Closure-Foam.

Available In:

- Ag Panel Inside
- Ag Panel Outside
- Ag Panel Outside Vented
- R Panel Inside
- R Panel Outside
- R Panel Outside Vented



Smart Vent

- Lower, custom fit profile
- Custom-cut profiles for snug fit
- Helps reduce utility cost.
- Moisture and pest barrier.
- Easy to installation.
- Non-obstructive appearance.
- Superior net-free ventilation reduced condensation




COVENT®

An all in one exhaust fan vent designed for metal roofs. CoVent is ideal for interior exhaust fans equipped with a 3" or 4" flex hose. This exhaust vent is intended for bathroom and attic venting. CoVent is not designed for dryer vents. Packed ready for installation.



RV35 Ridge-Vent

10' long low profile ventilator



- 1/2" Galvanized Mesh
- All Exposed Edges Hemmed
- Rain Diverter (Metal)
- Continuous Drainage Space
- 2" Nailing Flange Ideal for large attic or entire building ventilation such as horse, cattle or poultry buildings
- 3-1/2" unrestricted throat with 36 sq. inches of free area per lineal foot
- 13-1/4" overall coverage, with wider flanges available
- Use in conjunction with an equal area of vented soffit material or louvers for maximum air flow (36 sq in per lineal foot, 2.5 sq ft per vent)



9-12" Throat Commercial Ventilator

10' long ventilator

- 10' Long Ventilator
- 1/2" Galvanized Mesh
- All Exposed Edges Hemmed
- Rain Diverter (metal)
- Continuous Draining Space
- 2" Nailing Flange
- Ideal for large attics or entire building ventilation such as warehouses and industrial buildings



HydraShell Premium Underlayment

Hydra Shell underlayment is among the safest, strongest and best-performing underlayment's on the market. Woven of heavyweight polymer fabric, Premium underlayment offers superior strength and durability, steep-slope traction, water resistant, a wrinkle free surface, and resistance to UV breakdown. The textured woven fabric surface offers dynamic traction and is ideal for steep slopes in a variety of weather conditions. Hydra Shell Premium is rated for commercial and residential applications using plastic caps and roofing nails (3/8" head), and is ideal for roof underlayment for metal, tile, slate and variety of other sloped roofing.

Roll Size: 48" x 250'

Lifetime Limited Warranty.

- Safer: Skid-resistant polymer coating and proprietary Fiber Claw™ walking surface offers dynamic steep slope traction.
- Stronger than Type 15 or 30 felt and easier to handle during installation.
- Lighter than Type 15 or 30 felt and easier to handle during installation.
- Won't buckle, warp, or crack: Superior lay-flat properties and water resistance keeps HydraShell™ Premium from warping, wrinkling, and cracking in cold weather.





HydraShell Premium Ice and Water Underlayment

Roll Size: 36" x 67' (55lbs)



Lifetime Limited Warranty.

Metal to Wood Fasteners




Item	Head Style	Drill Point	PCS/Box	LBS / Bag
3/4" Stitch	1/4" Hex	Sharp Point	3000	25.9
1" High Low	1/4" Hex	T-17	3000	26.6
1-1/2" High Low	1/4" Hex	T-17	2500	27.8
2" High Low	1/4" Hex	T-17	2000	26.4
3" High Low	1/4" Hex	T-17	1000	18.3

Metal to Metal Fasteners




Item	Head Style	Drill Point	PCS/Box	LB / Box
7/8" Stitch	5/16" Hex	#1	2500	31.4
1-1/4" Self-Driller	5/16" Hex	#5	2500	36.3
2" Self-Driller	5/16" Hex	#5	1500	29.3

3" Deck Screws




Item	Head Style	Drill Point	PCS/Box	LBS/ Box
3" Deck Screws	T-25	T-17	1720	25

Pop Rivets




Item	Diameter	Length	PCS/Box	LB/ Box
Pop Rivets	1/8"	1-1/3"	10,000	30.2

Pan Head Wood Fastener



Item	Head Style	Drill Point	PCS/Box	PCS / Bag
1" Pan Head Wood Screw	Phillips / Square	Sharp Point	5,000	250
1-1/2" Pan Head Wood Screw	Phillips / Square	Sharp Point	2,500	250

Pan Head Self-Driller Fastener




Item	Head Style	Drill Point	PCS/Box	PCS / Box
1" Pan Head Self-Driller	Phillips / Square	Self-Driller	5,000	250
1-1/2" Pan Head Self-Driller	Phillips / Square	Self-Driller	2,500	250



Snow Defender®

Our stainless steel Snow Defender® line is made from quality-grade and heavy-gauge stainless steel that will not corrode. Our non-metal guards are made from Polycarbonate Lexan™, making them durable and resistant to damage from UV rays. Our stainless steel Snow Defender line is backed by a 15-year warranty, and is manufactured from start to finish in the United States.



**10
YEAR**
LIGHT TRANSMISSION
GUARANTEE

**THREE
YEAR**
WEATHER BREAKAGE
WARRANTY

Polycarbonate Panel

Polycarbonate panels deliver excellent light transmission, providing free natural light energy that helps brighten interiors, improve livestock productivity, and reduce overall building operating costs. Engineered for durability, these panels are damage- and impact-resistant—up to 200 times stronger than glass—while remaining lightweight and easy to handle and install. They offer high optical clarity, long-lasting UV protection, reliable performance in extreme temperatures, strong chemical resistance, and excellent fire performance.

Available in:

- 12' R Panel Profile Clear
- 12' R Panel Profile White
- 12' Ag Panel Profile Clear
- 12' Ag Panel Profile White
- 24' Wide Ridge Cap Clear
- 24' Wide Ridge Cap White



Cupolas

Cupola Sizes:

- 2x2
- 3x3
- 4x4
- 6x6

Window Options

- White
- Black

Specify pitch of roof

Specify colors

- Base
- Sides
- Roof

Louvered sides or windowed sides



Standing Seam Backer Rod

Standing Seam backer Rod is a flexible, extruded closed cell foam product that is 5/8" diameter and comes with adhesive backing. Many installers use backer rod to help prevent oil canning of non-striated standing seam metal roof panels. Our Standing Seam backer rod is an innovative product that comes with an adhesive backing for saving a time saving way to apply backer rod to the panels. Backer Rod can be easily trimmed to the precise size needed for upcoming Standing Seam Projects.

Available in:


- 1500' Rolls

Relieves internal stresses and waviness.

Easy to install.

Helps minimize Oil Canning.

Closed-cell Foam.




Box Gutter Expansion Joint

- Expandable edge strips flashing in grey
- Flashes hi-rib and standing-seam profiles
- Stretch and form to fit and seal
- Flash between dissimilar materials
- Ideal for square ducts, chimneys, skylights
- 20-year warranty.

Roll Size:

- 9" wide X 12', 33' and 50' length



Now Available



Malco
Work. Perform. Outlast.





BUILT TO LAST DELIVERED FAST



Visit us at www.championmetalsupply.com
or call (319) 331-1618



CMS-MM-260121-A2

2527 Highway 22
Riverside, IA 52327

1000 Ferguson Dr
Corsicana, TX 75110